



MET ONE 7000 Series Remote Airborne Particle Counters

Highest accuracy non-viable particle monitoring for EC/FDA compliance



Be Right™

The MET ONE 7000 remote airborne particle counters provide the most accurate continuous monitoring for the aseptic and sterile pharmaceutical production environments

Enhanced accuracy

ISO 21501 certified calibration provides data accuracy and repeatability

Built-in user notification

For particle monitoring events enables instant troubleshooting

System integration

Integrates to any FMS system with flexible communication options



Protected sensor

VHP tolerant optics, washdown resistant enclosure protects from accidental exposure to harmful disinfecting chemicals

Lowest cost of ownership

Proven reliable Long Life Laser™ diode

Reduced calibration time

Quick connect feature reduces time and cost of routine calibration



MET ONE 7000 remote particle counters are designed using patented technology to comply with new ISO 21501 calibration requirements that ensure measuring 0.5 μm to 5.0 μm particles with accuracy and repeatability. With flexible communication and OPC server options, the MET ONE 7000 easily integrates to any Facility Monitoring System. Built-in indication lights notify users of counter status and particle events such as reaching an alarm or alert level, eliminating the need to install additional hardware in the sterile environment.

Specially selected optical component materials and effectively sealed 316L stainless-steel enclosure make the MET ONE 7000 tolerant to typical VHP based disinfecting cycles and washdown processes used in cleanrooms. Features such as quick-connect cables and tubing reduce instrument removal and reinstallation time during routine calibration and maintenance work. Built with Long Life Laser™ technology and supported by dependable after sales support from Hach, the MET ONE 7000 minimizes cost of ownership and offers unparalleled user experience in product quality and reliability.

Specifications

<i>Light Source</i>	Long Life Laser™ diode
<i>Weight</i>	AC version: 3.96 kg (8.7 lbs) DC version: 3.91 kg (8.6 lbs)
<i>Dimensions</i>	22.9 W x 12.5 D x 16.0 H cm (9.02 x 4.92 x 6.3 inches)
<i>Enclosure</i>	316L stainless-steel sealed enclosure with sealed connectors suitable for washdown area
<i>Status Indicator</i>	Multi-colored LED for normal status, count alarm, count alert, sensor failure, flow failure or communication failure
<i>Power Requirements</i>	24 VDC ±10% or 100 to 230 VAC 50/60 Hz
<i>Power Consumption</i>	Ethernet unit: 6.9 W for DC, 8.9 W for AC maximum Serial unit: 5.9 W for DC, 7.6 W for AC maximum Analog unit: 6.1 W for DC, 7.9 W for AC maximum Wireless unit: 9.7 W DC, 12.5 W AC maximum
<i>Operating Temperature</i>	10 to 32 °C (50 to 90 °F), 5 to 95% relative humidity, non-condensing
<i>Storage Temperature</i>	-40 to 70 °C (-40 to 158 °F), 5 to 98% relative humidity, non-condensing
<i>Signal Output Options</i>	Ethernet or Wireless with TCP/IP protocol Serial RS-485 with Modbus RTU or FXB communication protocol Analog 4–20 mA
<i>Vacuum Requirements</i>	At least 40.6 cm (16 inches) Hg
<i>Number of Size Channels</i>	Standard 2 or Optional 4
<i>Flow Control</i>	Through critical orifice
<i>Isolation Valve</i>	Built-in solenoid valve
<i>Coincidence Loss</i>	Model 7005: 5% at 2,000,000 particles/ft ³ (70,600,000 particles/m ³) Model 7015: 5% at 400, 000 particle/ft ³ (14,000,000 particles/m ³)

False Count Rate
Accessories Included

How To Order

One or less in five minutes
Mounting Plate, Isokinetic Probe, Wall Plate,
Connector Umbilical Cables and Tubing, Operator Manual

20887_5-N F- - -

0	= DC Power Cord
B	= Type B AC Power Cord (N. America)
D	= Type D AC Power Cord (India)
E	= Type E AC Power Cord (Europe)
G	= Type G AC Power Cord (UK)
J	= Type J AC Power Cord (Switzerland)
D	= 24 VDC Input Power
A	= 100~230 VAC 50/60 HZ Input Power
A	= Analog 4~20 mA
E	= Ethernet
S	= Serial RS-485
W	= Wireless*
F	= With Flow Measurement
N	= No Built-in Pump
5	= 0.5 µm Minimum Sensitivity
0	= 0.1 CFM
1	= 1.0 CFM

Optional Accessories

Optional 4-Channel Setting
Purge Filters, 1.0 CFM 1/4 Tube and 0.1 CFM 1/8 Tube
Isokinetic Probes, 0.1 CFM and 1.0 CFM
Cable, Service Port Connector with RS-232 Converter
Relative Humidity/Temperature Probe
Brackets, for RH/Temp Probe and LED Indicator Stack/Isokinetic Probe
Remote Indicator Light Assembly
Cable Assembly, 3 m for Remote Indicator Light Assembly
Power Supply Unit, 24 VDC @ 5.0 A, Universal Input for FMS

For a comprehensive parts and accessories list, please refer to the user manual.
* Wireless option is available in limited number of countries. Please contact your Hach sales representative.

At Hach, it's about learning from our customers and providing the right answers.

Keep it pure.

Make it simple.

Be right.

For current price information, technical support, and ordering assistance, contact the Hach office or distributor serving your area.

In the United States, contact:

HACH COMPANY World Headquarters
PO Box 608
Loveland, Colorado 80539 USA
Telephone: 800-866-7889
Fax: 970-461-3914
E-mail: customersupport@hach.com
www.particle.com

U.S. exporters and customers in Canada, Latin America, sub-Saharan Africa, Asia, and Australia/New Zealand, contact:

HACH COMPANY World Headquarters
PO Box 608
Loveland, Colorado 80539 USA
Telephone: 970-663-9760
Fax: 970-461-3914
E-mail: intl@hach.com
www.particle.com

In Europe, the Middle East, and Mediterranean Africa, contact:

HACH LANGE GmbH
Willstätterstraße 11
D-40549 Düsseldorf, GERMANY
Tel: +49 (0) 211 5288-0
Fax: +49 (0) 211 5288-143
E-mail: info@hach-lange.de
www.particle.com



Lit. No. 5237
G9 Printed in USA
© Hach Company 2009. All rights reserved.

In the interest of improving and updating its equipment, Hach Company reserves the right to alter specifications to equipment at any time.



Be Right™