

HIAC PM4000

On-line Liquid Particle Monitor

Features

- Long life laser diode for exceptional performance and instrument life
- Real-time contamination and condition information for quicker decision making
- High temperature and pressure capabilities for harsh environments

Applications

- Total productive maintenance strategy (TPM)
- Predictive maintenance (PdM)
- Trend wear debris level assessment
- System dynamic analysis

Extend machine life, reduce downtime

Constructed for harsh environments, the HIAC PM4000 excels in high pressure and high temperature applications and offers carefree maintenance. The large flow path minimizes blockages during operation; the lack of moving parts makes maintenance trouble-free. The HIAC PM4000 on-line particle monitor serves a wide range of industrial and mobile applications: multipoint system monitoring as well as point-of-use applications including hydraulic presses and machines, filter carts, fluid fill stations, hydraulic power units, reclamation stations, and component test stands.

Simple, trouble-free, and affordable: the HIAC PM4000 allows you to spend more time preventing problems and less time fixing them.



Particle contamination levels provide easy analysis of a machine's condition. With hydraulics and high-speed rotational machinery, particle contamination leads to machine failure, downtime, and maintenance costs. Detecting failure mechanisms such as early detection of oil contaminants allows maintenance personnel to increase machine life and reliability. Hach's cost-effective HIAC PM4000-xx, which consists of the PT4000-x Particle Transducer and the IM4000-x Computer/PLC Interface, monitors particle contamination levels to alert personnel to small problems that could become bigger ones.



Be Right™

Specifications

<i>Sizes</i>	4, 6, 14, and 21 µm (ISO MTD)
<i>Light Source</i>	Laser diode
<i>Performance Verification</i>	Optional validation certificate available (ISO MTD at 2.8 mg/L concentration)
<i>Reproducibility</i>	0.5 ISO code (min. concentration ISO MTD 2.8 mg/L, max. ISO code = 24)
<i>Display</i>	Optional local display presents ISO codes, HIAC codes and alarms
<i>Power</i>	9 to 36 VDC, 150 mA (power must be supplied to instrument for operation)
<i>Output</i>	RS-232, RS-485, 0 to 5 volts, Modbus, alarms, local and remote displays
<i>Reports</i>	ISO 4406 and codes for 4, 6, 14, 21 µm (ISO MTD), particles/mL
<i>Fitting Connections</i>	SAE -4 and -8
<i>Sensor Flow Rate</i>	50 to 500 mL/min (0.01 to 0.1 gal/min) through view area; All units except the PT4000-3 offer integrated flow rate controllers
<i>Fluid Compatibility</i>	Hydraulic and lubrication oils, mineral, synthetic (Phosphate Ester option)
<i>Viscosity</i>	2 cSt (32 SUS) to 424 cSt (viscosities tested at ambient temperature: 25°C +/- 2 degrees)
<i>Environment</i>	Operating Temperature -10 to 60°C (-14 to 140°F) Storage Temperature -40 to 85°C (-40 to 185°F) 97% relative humidity, non-condensing
<i>IP Rating</i>	66
<i>Accessories Included</i>	DDE Software, 6.1 m (20 ft) Fiber Optic Cable, Operator's Manual (with PM4000-xx only, not included with PT4000-x)

Model PT4000-x Particle Transducer

Internal Flow Control Inhibitor

- 1 High pressure 27.6 to 482.5 bar (400 to 7,000 psi)
- 4 High pressure 27.6 to 482.5 bar (400 to 7,000 psi) with local display
- 7 Moderate pressure 3.4 to 82.7 bar (100 to 1200 psi)
- 8 Moderate pressure 3.4 to 82.7 bar (100 to 1200 psi) with local display
- 9 Low pressure 1.4 to 6.9 bar (20 to 200 psi)
- 0 Low pressure 1.4 to 6.9 bar (20 to 200 psi) with local display

Internal Check Flow Control

- 2 3.8 to 37.9 L/min (1 to 10 gal/min), 1.4 to 482.5 bar (20 to 7000 psi)
- 5 3.8 to 37.9 L/min (1 to 10 gal/min), 1.4 to 482.5 bar (20 to 7000 psi)
with local display

No Integrated Flow Control

- 3 50 to 500 mL/min (0.01 to 0.1 gal/min), 1.4 to 482.5 bar (20 to 7,000 psi)
- 6 50 to 500 mL/min (0.01 to 0.1 gal/min), 1.4 to 482.5 bar (20 to 7,000 psi)
with local display

Model IM4000-x Computer/PLC Interface

- 1 RS-232 dongle
- 3 Modbus, RS-232/RS-485, 0 to 5 volt
- 4 Remote LED display with programmable contamination alarm levels, dry contact closure (triggers on alarm)
- 5 Remote LED display with programmable cleanliness alarm levels, dry contact closure (triggers on alarm)

Optional Accessories

Phosphate Ester Compatibility
Minimess Sampling Port SAE -4
Minimess Microbore Sampling Hose



Lit. No. 5221
G9 Printed in USA
© Hach Company 2009. All rights reserved.
In the interest of improving and updating its equipment, Hach Company reserves the right to alter specifications to equipment at any time.

At Hach, it's about learning from our customers and providing the right answers.

Keep it pure.

Make it simple.

Be right.

For current price information, technical support, and ordering assistance, contact the Hach office or distributor serving your area.

In the United States, contact:

HACH COMPANY World Headquarters
PO Box 608
Loveland, Colorado 80539 USA
Telephone: 800-866-7889
Fax: 970-461-3914
E-mail: customersupport@hach.com
www.particle.com

U.S. exporters and customers in Canada, Latin America, sub-Saharan Africa, Asia, and Australia/New Zealand, contact:

HACH COMPANY World Headquarters
PO Box 608
Loveland, Colorado 80539 USA
Telephone: 970-663-9760
Fax: 970-461-3914
E-mail: intl@hach.com
www.particle.com

In Europe, the Middle East, and Mediterranean Africa, contact:

HACH LANGE GmbH
Willstätterstraße 11
D-40549 Düsseldorf, GERMANY
Tel: +49 (0) 211 5288-0
Fax: +49 (0) 211 5288-143
E-mail: info@hach-lange.de
www.particle.com



Be Right™